

**AGMA CLASS II
EXPLOSION PROOF
0.5 HP**

AGMA CLASS II EXPLOSION PROOF 0.5 HP					C-FACE			REDUCER w/NEMA C-FACE ADAPTER FRAME 56C
					NORD OR OTHER "INQUIRE"	BALDOR MOTOR		
						DRILL RIG DUTY VM7006-I 56C TEFC 230/460V CONSTANT	IDXM7006 56C TEFC 230/460V 10:1 CT	
RPM	INCH LBS	AGMA S.F.	GEAR RATIO	GEAR MODEL				
1,274	25	8.5	1.35	SK11E		\$ 1,290	\$ 1,714	\$ 485
1,117	28	8.3	1.54					
950	33	8.0	1.81					
843	37	7.7	2.04					
741	43	7.4	2.32					
608	52	6.9	2.83					
583	54	7.2	2.95	SK02		1,311	1,735	506
509	62	6.9	3.38					
442	71	6.6	3.89					
408	77	6.0	4.22					
357	88	5.8	4.82					
309	102	5.0	5.57					
282	112	4.5	6.10					
250	126	4.3	6.89					
221	143	3.9	7.80					
210	150	3.7	8.19					
185	170	3.4	9.28					
173	182	3.1	9.95					
153	206	2.9	11.27					
134	235	2.7	12.82					
108	292	2.2	15.95					
103	307	4.5	16.73	SK12		1,344	1,768	539
92	344	4.2	18.79					
84	377	1.7	20.59	SK02		1,311	1,735	506
81	390	3.8	21.28	SK12		1,344	1,768	539
74	424	1.6	23.13	SK02		1,311	1,735	506
71	447	1.8	24.39					
66	475	2.6	25.92	SK12		1,344	1,768	539
63	504	1.5	27.52	SK02		1,311	1,735	506
59	534	2.1	29.15	SK12		1,344	1,768	539
58	542	1.5	29.61	SK02		1,311	1,735	506
55	571	2.6	31.19	SK12		1,344	1,768	539
49	643	2.1	35.07					
45	702	2.3	38.31					
40	789	1.8	43.09					
37	841	3.1	45.90	SK22		1,500	1,924	695
36	877	1.8	47.87	SK12		1,344	1,768	539
32	986	1.6	53.84					
31	1,013	2.8	55.28	SK22		1,500	1,924	695
25	1,279	1.8	69.81					
20	1,581	1.4	86.30					
19	1,621	1.9	88.45	SK23		1,814	2,238	1,009
17	1,843	1.6	100.60					

**AGMA CLASS II
EXPLOSION PROOF
0.75 HP**

AGMA CLASS II EXPLOSION PROOF 0.75 HP					C-FACE			REDUCER w/NEMA C-FACE ADAPTER FRAME 56C
					NORD OR OTHER "INQUIRE"	BALDOR MOTOR		
						DRILL RIG DUTY VM7010-I 56C TEFC 230/460V CONSTANT	IDXM7010 56C TEFC 230/460V 10:1 CT	
RPM	INCH LBS	AGMA S.F.	GEAR RATIO	GEAR MODEL				
1,278	37	5.6	1.35	SK11E		\$ 1,380	\$ 1,741	\$ 485
1,120	42	5.5	1.54					
953	50	5.3	1.81					
846	56	5.1	2.04					
744	64	4.9	2.32					
610	78	4.6	2.83					
585	81	4.7	2.95	SK02		1,401	1,762	506
510	93	4.5	3.38					
443	107	4.3	3.89					
409	116	3.9	4.22					
358	132	3.8	4.82					
310	153	3.3	5.57					
283	167	3.0	6.10					
250	189	2.8	6.89					
221	214	2.6	7.80					
211	224	2.5	8.19					
186	254	2.2	9.28					
173	273	2.1	9.95					
161	293	4.0	10.70	SK12		1,434	1,795	539
153	309	1.9	11.27	SK02		1,401	1,762	506
135	351	1.7	12.82					
129	367	3.6	13.39	SK12		1,434	1,795	539
108	437	1.4	15.95	SK02		1,401	1,762	506
103	458	2.9	16.73	SK12		851	922	604
92	515	2.7	18.79					
81	583	2.5	21.28					
70	678	3.2	24.73	SK22		1,590	1,951	695
67	710	1.7	25.92	SK12		1,434	1,795	539
59	803	3.2	29.31	SK22		1,590	1,951	695
55	855	1.7	31.19	SK12		1,434	1,795	539
49	974	3.0	35.55	SK22		1,590	1,951	695
40	1,173	2.5	42.82					
38	1,258	2.0	45.90					
31	1,515	1.9	55.28					
30	1,576	3.4	57.53	SK32		1,814	2,175	919
27	1,761	3.2	64.26					
24	1,994	2.5	72.76					
21	2,227	2.0	81.27					
20	2,416	1.9	88.18	SK33N		1,953	2,314	1,058
15	3,074	1.6	112.18					

AGMA CLASS II EXPLOSION PROOF 1 HP					C-FACE			REDUCER w/NEMA C-FACE ADAPTER FRAME 140TC
					NORD OR OTHER "INQUIRE"	BALDOR MOTOR		
						DRILL RIG DUTY VM7014T-I 143TC TEFC 230/460V CONSTANT	IDXM7014T 143TC TEFC 230/460V 10:1 CT	
RPM	INCH LBS	AGMA S.F.	GEAR RATIO	GEAR MODEL				
1,278	49	4.1	1.35	SK11E		\$ 1,499	\$ 1,884	\$ 485
1,120	56	3.9	1.54					
953	66	3.8	1.81					
846	75	3.7	2.04					
744	85	3.5	2.32					
610	103	3.3	2.83					
585	108	3.4	2.95	SK02		1,521	1,906	\$ 507
510	123	3.3	3.38					
443	142	3.1	3.89					
409	154	2.8	4.22					
358	176	2.7	4.82					
310	204	2.4	5.57					
283	223	2.2	6.10					
250	252	2.0	6.89					
237	266	3.9	7.28	SK12		1,582	1,967	568
221	285	1.9	7.80	SK02		1,521	1,906	507
220	287	3.7	7.85	SK12		1,582	1,967	568
211	299	1.8	8.19	SK02		1,521	1,906	507
202	313	3.5	8.56	SK12		1,582	1,967	568
186	339	1.6	9.28	SK02		1,521	1,906	507
179	353	3.2	9.65	SK12		1,582	1,967	568
173	364	1.5	9.95	SK02		1,521	1,906	507
161	391	2.9	10.70	SK12		1,582	1,967	568
153	412	1.4	11.27	SK02		1,521	1,906	507
129	489	2.6	13.39	SK12		1,582	1,967	568
103	611	2.1	16.73					
92	687	2.0	18.79					
81	777	1.8	21.28					
70	904	2.3	24.73	SK22		1,709	2,094	695
59	1,071	2.3	29.31					
49	1,299	2.1	35.55					
45	1,416	2.7	38.76	SK32		1,933	2,318	919
40	1,564	1.8	42.82	SK22		1,709	2,094	695
38	1,677	1.5	45.90					
30	2,102	2.5	57.53	SK32		1,933	2,318	919
27	2,348	2.3	64.26					
25	2,562	3.6	70.12	SK43		2,528	2,913	1,514
24	2,658	1.8	72.76	SK32		1,933	2,318	919
22	2,921	3.4	79.96					
21	2,969	1.5	81.27	SK43		2,528	2,913	1,514
20	3,222	1.4	88.18					
18	3,469	3.0	94.96	SK43		2,528	2,913	1,514
16	3,928	2.4	107.51					

AGMA CLASS II EXPLOSION PROOF 1.5 HP					"INQUIRE"	C-FACE		REDUCER w/NEMA C-FACE ADAPTER FRAME 140TC	
						NORD OR OTHER	BALDOR MOTOR		
							DRILL RIG DUTY VM7034T-I 145TC TEFC 230/460V CONSTANT		IDXM7034T 145TC TEFC 230/460V 10:1 CT
RPM	INCH LBS	AGMA S.F.	GEAR RATIO	GEAR MODEL					
1,278	74	3.7	1.35	SK11E		\$ 1,578	\$ 1,934	\$ 485	
1,120	84	3.5	1.54						
953	99	3.3	1.81						
846	112	3.2	2.04						
744	127	3.2	2.32						
610	155	3.0	2.83						
585	162	2.4	2.95	SK02		1,600	1,956	507	
510	185	2.4	3.38						
443	213	2.1	3.89						
433	218	3.9	3.98	SK12		1,661	2,017	568	
409	231	1.9	4.22	SK02		1,600	1,956	507	
399	237	4.0	4.32	SK12		1,661	2,017	568	
384	246	3.8	4.49						
358	264	1.9	4.82	SK02		1,600	1,956	507	
350	270	3.7	4.93	SK12		1,661	2,017	568	
310	305	1.6	5.57	SK02		1,600	1,956	507	
298	317	3.3	5.79	SK12		1,661	2,017	568	
264	358	3.0	6.53						
250	378	1.4	6.89	SK02		1,600	1,956	507	
237	399	2.6	7.28	SK12		1,661	2,017	568	
220	430	2.6	7.85						
202	469	2.4	8.56						
179	529	2.2	9.65						
161	586	1.9	10.70						
158	597	3.8	10.89	SK22		1,788	2,144	695	
141	669	3.7	12.20						
129	734	1.7	13.39	SK12		1,661	2,017	568	
117	805	3.6	14.69	SK22		1,788	2,144	695	
103	917	1.4	16.73	SK12		1,661	2,017	568	
86	1,098	2.2	20.03	SK22		1,788	2,144	695	
73	1,301	2.0	23.74						
70	1,355	1.5	24.73						
65	1,456	2.6	26.57	SK32		2,012	2,368	919	
63	1,493	3.2	27.24						
60	1,578	2.0	28.80	SK22		1,788	2,144	695	
59	1,606	1.5	29.31						
57	1,668	2.6	30.43	SK32		2,012	2,368	919	
55	1,708	2.6	31.16						
52	1,811	1.8	33.05						
49	1,948	1.4	35.55	SK22		1,788	2,144	695	
46	2,040	2.5	37.23	SK32		2,012	2,368	919	
45	2,124	1.8	38.76						
37	2,535	2.3	46.25						
37	2,538	1.8	46.31						
30	3,153	1.7	57.53						
28	3,324	2.6	60.66	SK42		2,417	2,773	1,324	
27	3,522	1.5	64.26	SK32		2,012	2,368	919	
23	4,103	2.2	74.87	SK42		2,417	2,773	1,324	
20	4,664	1.5	85.10						

**AGMA CLASS II
EXPLOSION PROOF
2 HP**

AGMA CLASS II EXPLOSION PROOF 2 HP					C-FACE			REDUCER w/NEMA C-FACE ADAPTER FRAME 140TC
					"INQUIRE"	BALDOR MOTOR		
						DRILL RIG DUTY VM7037T-I 145TC TEFC 230/460V CONSTANT	IDXM7037T 145TC TEFC 230/460V 10:1 CT	
RPM	INCH LBS	AGMA S.F.	GEAR RATIO	GEAR MODEL				
1,278	99	3.2	1.35	SK11E		\$ 1,667	\$ 2,070	\$ 485
1,120	113	3.1	1.54					
953	132	3.0	1.81					
846	149	2.8	2.04					
744	170	2.4	2.32					
610	207	2.2	2.83					
585	216	1.8	2.95	SK02		1,689	2,092	507
510	247	1.8	3.38					
443	284	1.6	3.89					
409	308	1.4	4.22					
358	352	1.4	4.82					
350	360	2.7	4.93	SK12		1,750	2,153	568
298	423	2.5	5.79					
264	477	2.3	6.53					
251	501	3.1	6.86	SK22		1,877	2,280	695
237	532	2.0	7.28	SK12		1,750	2,153	568
228	553	2.9	7.57	SK22		1,877	2,280	695
220	574	1.9	7.85	SK12		1,750	2,153	568
203	620	2.8	8.48	SK22		1,877	2,280	695
202	626	1.8	8.56	SK12		1,750	2,153	568
179	705	1.6	9.65					
161	782	1.5	10.70					
158	796	2.9	10.89	SK22		1,877	2,280	695
141	891	2.8	12.20					
117	1,073	2.7	14.69					
103	1,224	2.4	16.75					
92	1,364	3.0	18.67	SK32		2,101	2,504	919
86	1,464	1.7	20.03	SK22		1,877	2,280	695
83	1,513	2.9	20.70	SK32		2,101	2,504	919
75	1,689	2.9	23.12					
73	1,735	1.6	23.74	SK22		1,877	2,280	695
65	1,942	1.9	26.57	SK32		2,101	2,504	919
60	2,104	1.5	28.80	SK22		1,877	2,280	695
57	2,224	2.0	30.43	SK32		2,101	2,504	919
49	2,576	4.1	35.25	SK42		2,506	2,909	1,324
46	2,720	1.8	37.23	SK32		2,101	2,504	919
37	3,380	1.7	46.25					
34	3,725	2.5	50.98	SK42		2,506	2,909	1,324
30	4,258	2.3	58.27	SK43		2,696	3,099	1,514
28	4,433	1.9	60.66	SK42		2,506	2,909	1,324
23	5,471	1.7	74.87					
22	5,843	1.9	79.96	SK43		2,696	3,099	1,514
20	6,351	2.3	86.92	SK53		3,336	3,739	2,154
18	6,978	2.7	95.49					
16	7,736	2.5	105.87					

**AGMA CLASS II
EXPLOSION PROOF
3 HP**

AGMA CLASS II EXPLOSION PROOF 3 HP					C-FACE				REDUCER w/NEMA C-FACE ADAPTER FRAME 180TC
					NORD OR OTHER "INQUIRE"	BALDOR MOTOR			
						DRILL RIG DUTY VM7042T-I 182TC TEFC 230/460V CONSTANT	IDXM7142T 182TC TEFC 230/460V 2:1 CT	IDXM7542T 182TC TEFC 230/460V 10:1 CT	
RPM	INCH LBS	AGMA S.F.	GEAR RATIO	GEAR MODEL					
1,278	148	3.0	1.35	SK11E		\$ 2,065	\$ 2,274	\$ 2,358	\$ 550
1,120	169	2.6	1.54						
953	198	2.4	1.81						
846	224	2.3	2.04						
744	254	1.6	2.32						
610	310	1.5	2.83						
583	324	2.8	2.96	SK12		2,111	2,320	2,404	596
509	372	2.6	3.39						
433	436	2.3	3.98						
399	474	2.1	4.32						
384	492	2.1	4.49						
373	506	2.6	4.62	SK22		2,242	2,451	2,535	727
350	540	1.9	4.93	SK12		2,111	2,320	2,404	596
333	568	2.4	5.18	SK22		2,242	2,451	2,535	727
298	635	3.0	5.79						
298	635	1.7	5.79	SK12		2,111	2,320	2,404	596
265	714	2.8	6.51	SK22		2,242	2,451	2,535	727
264	716	1.5	6.53	SK12		2,111	2,320	2,404	596
251	752	3.0	6.86	SK22		2,242	2,451	2,535	727
228	830	2.6	7.57						
203	929	2.4	8.48						
158	1,194	2.3	10.89						
141	1,337	2.1	12.20						
119	1,595	3.1	14.55	SK32		2,468	2,677	2,761	953
117	1,610	1.8	14.69	SK22		2,242	2,451	2,535	727
115	1,647	2.7	15.03	SK32		2,468	2,677	2,761	953
106	1,781	3.1	16.25						
104	1,826	2.5	16.66						
92	2,046	2.7	18.67						
83	2,269	2.5	20.70						
79	2,397	3.4	21.87	SK42		2,915	3,124	3,208	1,400
75	2,534	2.2	23.12	SK32		2,468	2,677	2,761	953
71	2,676	2.8	24.41	SK42		2,915	3,124	3,208	1,400
70	2,704	2.9	24.67						
63	2,986	1.8	27.24	SK32		2,468	2,677	2,761	953
59	3,210	2.8	29.29	SK42		2,915	3,124	3,208	1,400
57	3,339	2.8	30.46						
49	3,864	2.8	35.25						
42	4,526	2.3	41.29						
35	5,360	3.1	48.90	SK52		3,280	3,489	3,573	1,765
34	5,588	1.7	50.98	SK42		2,915	3,124	3,208	1,400
32	5,898	2.8	53.81	SK52		3,280	3,489	3,573	1,765
29	6,526	2.5	59.54						
24	7,825	1.8	71.39						
22	8,611	1.6	78.56						
20	9,527	1.6	86.92						
18	10,467	1.9	95.49	SK53		3,703	3,912	3,996	2,188
16	11,604	1.7	105.87						

**AGMA CLASS II
EXPLOSION PROOF
5 HP**

AGMA CLASS II EXPLOSION PROOF 5 HP					C-FACE				REDUCER w/NEMA C-FACE ADAPTER FRAME 180TC	REDUCER w/NEMA C-FACE ADAPTER FRAME 210TC
					NORD OR OTHER	BALDOR MOTOR				
						DRILL RIG DUTY VM7044T-I 184TC TEFC 230/460V CONSTANT	IDXM7144T 184TC TEFC 230/460V 2:1 CT	IDXM7544T 213TC TEFC 230/460V 10:1 CT		
RPM	INCH LBS	AGMA S.F.	GEAR RATIO	GEAR MODEL	"INQUIRE"					
1,199	263	2.0	1.46	SK21E		\$ 2,480	\$ 2,684	N/A	\$ 634	N/A
946	333	1.7	1.85							
841	375	2.1	2.08	SK31E		2,613	2,817	N/A	767	N/A
841	375	1.6	2.08	SK21E		2,480	2,684	N/A	634	N/A
723	436	1.5	2.42							
678	465	1.9	2.58	SK31E		2,613	2,817	N/A	767	N/A
627	502	2.2	2.79	SK22		2,573	2,777	N/A	727	N/A
591	533	1.7	2.96	SK12		2,442	2,646	N/A	596	N/A
516	610	1.6	3.39							
496	636	1.8	3.53	SK22		2,573	2,777	N/A	727	N/A
467	675	2.2	3.75	SK32		2,799	3,003	3,662	953	1,027
441	715	1.7	3.97	SK22		2,573	2,777	N/A	727	N/A
395	798	2.1	4.43	SK32		2,799	3,003	3,662	953	1,027
379	832	1.6	4.62	SK22		2,573	2,777	N/A	727	N/A
338	933	1.5	5.18							
331	951	2.3	5.28	SK32		2,799	3,003	3,662	953	1,027
318	990	1.9	5.50							
307	1,026	2.2	5.70							
302	1,043	1.8	5.79	SK22		2,573	2,777	N/A	727	N/A
269	1,172	1.7	6.51							
255	1,235	1.8	6.86							
231	1,363	1.6	7.57							
206	1,527	1.5	8.48							
179	1,765	1.9	9.80	SK32		2,799	3,003	3,662	953	1,027
161	1,961	1.4	10.89	SK22		2,573	2,777	N/A	727	N/A
149	2,109	1.9	11.71	SK32		2,799	3,003	3,662	953	1,027
120	2,620	1.9	14.55							
116	2,706	1.6	15.03							
108	2,926	1.9	16.25							
105	3,000	1.5	16.66							
94	3,362	1.6	18.67							
85	3,727	1.5	20.70							
80	3,938	2.1	21.87	SK42		3,246	3,450	4,115	1,400	1,480
72	4,396	1.7	24.41							
60	5,274	1.7	29.29							
57	5,485	1.7	30.46							
50	6,348	1.7	35.25							
49	6,488	1.9	36.03	SK52		3,611	3,815	4,475	1,765	1,840
46	6,924	2.1	38.45							
36	8,805	1.9	48.90							
33	9,690	1.7	53.81							
29	#####	1.5	59.54							
28	#####	2.3	62.87	SK63		4,927	5,131	5,786	3,081	3,151
23	#####	2.1	77.46							
20	#####	1.7	87.06							
16	#####	1.6	107.89							

**AGMA CLASS II
EXPLOSION PROOF
7.5 HP**

AGMA CLASS II EXPLOSION PROOF 7.5 HP					C-FACE				REDUCER w/NEMA C-FACE ADAPTER FRAME 210TC
					NORD OR OTHER "INQUIRE"	BALDOR MOTOR			
						DRILL RIG DUTY CM7047T-I 213TC TEFC 230/460V CONSTANT	IDXM7147T 213TC TEFC 230/460V 2:1 CT	IDXM7547T 215TC TEFC 230/460V 10:1 CT	
						RPM	INCH LBS	AGMA S.F.	
1,266	373	3.3	1.39	SK31E		\$ 2,824	\$ 3,419	N/A	\$ 841
1,000	473	2.8	1.76						
846	559	2.6	2.08						
682	693	2.3	2.58						
595	795	3.4	2.96	SK32		3,010	3,605	N/A	1,027
469	1,007	3.2	3.75						
397	1,190	2.9	4.43						
333	1,418	3.4	5.28						
320	1,477	2.6	5.50						
309	1,531	3.2	5.70						
279	1,695	2.9	6.31						
242	1,955	3.5	7.28	SK42		3,463	4,058	5,184	1,480
223	2,122	2.7	7.90	SK32		3,010	3,605	N/A	1,027
211	2,245	2.3	8.36						
207	2,283	3.2	8.50	SK42		3,463	4,058	5,184	1,480
180	2,632	2.1	9.80	SK32		3,010	3,605	N/A	1,027
173	2,739	3.2	10.20	SK42		3,463	4,058	5,184	1,480
150	3,145	2.0	11.71	SK32		3,010	3,605	N/A	1,027
143	3,298	3.2	12.28	SK42		3,463	4,058	5,184	1,480
131	3,612	4.6	13.45	SK52		3,823	4,418	5,544	1,840
126	3,760	4.5	14.00						
122	3,862	2.6	14.38	SK42		3,463	4,058	5,184 N/A N/A	1,480
116	4,061	2.7	15.12						
99	4,756	2.2	17.71						
98	4,813	1.8	17.92						
82	5,774	1.8	21.50						
81	5,823	2.8	21.68	SK52		3,823	4,418	5,544 N/A N/A	1,840
74	6,424	2.6	23.92						
73	6,465	2.3	24.07						
67	7,106	2.3	26.46						
61	7,748	2.3	28.85						
57	8,302	3.5	30.91	SK63		5,134	5,729	6,855	3,151
55	8,618	1.4	32.09	SK52		3,823	4,418	5,544	1,840
49	9,698	3.2	36.11	SK63		5,134	5,729	6,855	3,151
48	9,854	1.7	36.69	SK52		3,823	4,418	N/A	1,840
46	10,327	1.4	38.45						
44	10,842	1.5	40.37						
41	11,664	2.8	43.43	SK63		5,134	5,729	6,855	3,151
39	12,263	3.9	45.66	SK73		6,015	6,610	7,736	4,032
35	13,625	2.4	50.73	SK63		5,134	5,729	6,855	3,151
34	14,030	3.5	52.24	SK73		6,015	6,610	7,736	4,032
33	14,455	2.2	53.82	SK63		5,134	5,729	6,855	3,151
29	16,238	3.0	60.46	SK73		6,015	6,610	7,736	4,032
28	16,885	1.9	62.87	SK63		5,134	5,729	6,855	3,151
24	20,108	2.3	74.87	SK73		6,015	6,610	7,736	4,032
19	24,542	1.9	91.38						

**AGMA CLASS II
EXPLOSION PROOF
10 HP**

AGMA CLASS II EXPLOSION PROOF 10 HP					C-FACE					
					NORD OR OTHER "INQUIRE"	BALDOR MOTOR				
						DRILL RIG DUTY CM7170T-I 215TC TEFC 230/460V CONSTANT	IDXM7170T 215TC TEFC 230/460V 2:1 CT	IDXM7570T 254TC TEFC 230/460V 10:1 CT		
RPM	INCH LBS	AGMA S.F.	GEAR RATIO	GEAR MODEL						
1,248	505	3.0	1.41	SK41E		\$ 3,477	\$ 4,666	\$ 5,370	\$ 1,132	\$ 1,225
1,173	537	3.0	1.50							
1,080	584	2.9	1.63							
967	652	2.7	1.82							
822	766	2.6	2.14							
704	895	2.4	2.50							
595	1,060	2.5	2.96	SK32		3,372	4,561	N/A	1,027	N/A
469	1,343	2.4	3.75							
397	1,586	2.2	4.43							
333	1,891	2.5	5.28							
320	1,970	2.0	5.50							
309	2,041	2.4	5.70							
306	2,059	3.0	5.75	SK42		3,825	5,014	5,660	1,480	1,515
284	2,217	2.7	6.19							
265	2,381	2.9	6.65							
261	2,414	2.2	6.74	SK32		3,372	4,561	N/A	1,027	N/A
242	2,607	2.6	7.28	SK42		3,825	5,014	5,660	1,480	1,515
223	2,829	2.0	7.90	SK32		3,372	4,561	N/A	1,027	N/A
211	2,994	1.7	8.36							
207	3,044	2.4	8.50	SK42		3,825	5,014	5,660	1,480	1,515
180	3,509	1.6	9.80	SK32		3,372	4,561	N/A	1,027	N/A
173	3,653	2.4	10.20	SK42		3,825	5,014	5,660	1,480	1,515
143	4,397	2.4	12.28							
122	5,149	2.0	14.38							
116	5,414	2.0	15.12							
99	6,342	1.6	17.71							
99	6,378	2.6	17.81	SK52		4,185	5,374	6,021	1,840	1,876
98	6,417	1.4	17.92	SK42		3,825	5,014	5,660	1,480	1,515
90	7,019	2.4	19.60	SK52		4,185	5,374	6,021 N/A N/A	1,840	1,876 N/A N/A
81	7,764	2.1	21.68							
74	8,566	1.9	23.92							
73	8,619	1.7	24.07							
67	9,475	1.7	26.46							
61	10,331	1.7	28.85							
53	11,903	3.2	33.24	SK73		6,377	7,566	8,869	4,032	4,724
47	13,475	3.0	37.63							
41	15,552	2.1	43.43	SK63		5,496	6,685	8,091	3,151	3,946
35	18,166	1.8	50.73							
33	19,273	1.7	53.82							
29	21,651	2.3	60.46	SK73		6,487	7,676	8,979	4,142	4,834
24	26,811	1.7	74.87							
22	28,870	2.7	80.62	SK83		9,126	10,315	10,967	6,781	6,822
19	32,723	1.4	91.38	SK73		6,377	7,566	8,869	4,032	4,724
17	37,242	2.1	104.00	SK83		9,126	10,315	10,967	6,781	6,822

**AGMA CLASS II
EXPLOSION PROOF
15 HP**

AGMA CLASS II EXPLOSION PROOF 15 HP					C-FACE				REDUCER w/NEMA C-FACE ADAPTER FRAME 250TC
					NORD OR OTHER "INQUIRE"	BALDOR MOTOR			
						DRILL RIG DUTY CM7054T-I 254TC TEFC 230/460V CONSTANT	IDXM7054T 254TC TEFC 230/460V 2:1 CT	IDXM7554T 256TC TEFC 230/460V 10:1 CT	
RPM	INCH LBS	AGMA S.F.	GEAR RATIO	GEAR MODEL					
1,248	757	2.1	1.41	SK41E					
1,173	806	2.1	1.50						
1,080	876	2.0	1.63			\$ 5,318	\$ 5,272	\$ 6,600	\$ 1,225
967	978	2.0	1.82						
822	1,149	1.9	2.14						
704	1,343	1.8	2.50						
615	1,536	2.6	2.86	SK51E		5,534	5,488	6,816	1,441
583	1,622	3.4	3.02	SK42					
548	1,724	3.3	3.21						
503	1,880	3.2	3.50						
452	2,089	3.1	3.89						
384	2,460	2.9	4.58						
367	2,573	3.4	4.79			5,608	5,562	6,890	1,515
345	2,739	3.2	5.10						
329	2,874	2.6	5.35						
306	3,089	3.3	5.75						
284	3,325	2.9	6.19						
274	3,448	3.5	6.42	SK52		5,969	5,923	7,251	1,876
265	3,572	3.0	6.65	SK42		5,608	5,562	6,890	1,515
242	3,910	2.5	7.28						
229	4,136	3.4	7.70	SK52		5,969	5,923	7,251	1,876
207	4,566	2.1	8.50	SK42					
173	5,479	1.9	10.20			5,608	5,562	6,890	1,515
143	6,596	1.6	12.28						
131	7,225	2.3	13.45	SK52		5,969	5,923	7,251	1,876
126	7,520	1.8	14.00						
111	8,487	3.1	15.80	SK62		7,932	7,886	9,214	3,839
101	9,330	3.0	17.37	SK63		8,039	7,993	9,321	3,946
99	9,567	1.6	17.81	SK52		5,969	5,923	7,251	1,876
90	10,231	1.6	19.60						
85	11,156	2.4	20.77	SK63		8,039	7,993	9,321	3,946
82	11,317	1.4	21.68	SK52		5,969	5,923	7,251	1,876
67	14,116	2.0	26.28	SK63					
57	16,603	1.9	30.91			8,039	7,993	9,321	3,946
49	19,396	1.7	36.11						
41	23,328	1.4	43.43						
39	24,526	1.9	45.66	SK73					
34	28,060	1.8	52.24			8,817	8,771	10,099	4,724
29	32,476	1.5	60.46						
28	33,244	2.4	61.89	SK83		10,915	10,869	12,197	6,822
25	37,729	2.1	70.24						
24	38,927	3.0	72.47	SK93		13,622	13,576	14,904	9,529
22	43,305	1.8	80.62	SK83		10,915	10,869	12,197	6,822
19	50,137	2.5	93.34	SK93		13,622	13,576	14,904	9,529
17	55,863	1.5	104.00	SK83		10,915	10,869	12,197	6,822
16	58,624	1.8	109.14	SK93		13,622	13,576	14,904	9,529

**AGMA CLASS II
EXPLOSION PROOF
20 HP**

AGMA CLASS II EXPLOSION PROOF 20 HP					C-FACE				REDUCER w/NEMA C-FACE ADAPTER FRAME 250TC	REDUCER w/NEMA C-FACE ADAPTER FRAME 280TC
					NORD OR OTHER "INQUIRE"	BALDOR MOTOR				
						DRILL RIG DUTY CM7056T-I 256TC TEFC 230/460V CONSTANT	IDXM7056T 256TC TEFC 230/460V 2:1 CT	IDXM7556T M13G * 284TC TEFC 230/460V 10:1 CT		
RPM	INCH LBS	AGMA S.F.	GEAR RATIO	GEAR MODEL						
1,248	1,010	1.6	1.41	SK41E						
1,173	1,074	1.6	1.50							
1,080	1,167	1.5	1.63		\$ 5,979	\$ 6,476	\$ 11,014	\$ 1,225	\$ 2,156	
967	1,303	1.5	1.82							
822	1,533	1.4	2.14							
704	1,790	2.1	2.50	SK51E						
615	2,048	2.0	2.86		6,195	6,692	10,998	1,441	2,140	
583	2,163	2.5	3.02	SK42						
548	2,299	2.4	3.21		6,269	6,766	11,263	1,515	2,405	
503	2,507	2.4	3.50							
452	2,786	2.2	3.89							
431	2,922	2.6	4.08	SK52						
402	3,137	3.0	4.38		6,630	7,127	11,333	1,876	2,475	
382	3,302	2.5	4.61							
367	3,431	2.1	4.79	SK42		6,269	6,766	11,263	1,515	2,405
346	3,638	2.9	5.08	SK52		6,630	7,127	11,333	1,876	2,475
345	3,653	2.4	5.10	SK42						
329	3,832	1.9	5.35		6,269	6,766	11,263	1,515	2,405	
314	4,011	2.3	5.60	SK52						
304	4,147	2.8	5.79		6,630	7,127	11,333	1,876	2,475	
284	4,433	2.2	6.19	SK42		6,269	6,766	11,263	1,515	2,405
274	4,598	2.6	6.42	SK52		6,630	7,127	11,333	1,876	2,475
265	4,763	2.2	6.65	SK42						
242	5,214	1.8	7.28		6,269	6,766	11,263	1,515	2,405	
229	5,515	2.6	7.70	SK52						
199	6,324	2.3	8.83		6,630	7,127	11,333	1,876	2,475	
166	7,577	2.1	10.58							
152	8,301	2.7	11.59	SK62		8,593	9,090	12,739	3,839	3,881
131	9,633	1.7	13.45	SK52		6,630	7,127	11,333	1,876	2,475
126	9,969	2.5	13.92	SK62		8,593	9,090	12,739	3,839	3,881
126	10,027	1.7	14.00	SK52		6,630	7,127	11,333	1,876	2,475
111	11,316	2.4	15.80	SK62		8,593	9,090	12,739	3,839	3,881
101	12,440	2.2	17.37	SK63		8,700	9,197	12,846	3,946	3,988
97	12,992	2.1	18.14	SK62		8,593	9,090	12,739	3,839	3,881
85	14,875	1.9	20.77	SK63						
80	15,742	1.8	21.98		8,700	9,197	12,846	3,946	3,988	
67	18,822	1.5	26.28							
62	20,283	2.2	28.32	SK73		8,093	10,085	13,692	4,834	4,834
57	22,138	1.4	30.91	SK63		8,700	9,197	12,846	3,946	3,988
53	23,806	1.9	33.24	SK73						
47	26,950	1.6	37.63		9,478	9,975	13,621	4,724	4,763	
45	27,989	2.5	39.08	SK83						
40	31,785	2.5	44.38		10,191	12,183	15,790	6,932	6,932	
39	32,701	1.5	45.66	SK73		9,478	9,975	13,621	4,724	4,763
34	36,891	2.1	51.51	SK83						
28	44,325	1.8	61.89		11,576	12,073	15,981	6,822	7,123	
25	50,305	1.6	70.24							
24	51,903	2.3	72.47	SK93		14,283	14,780	18,428	9,529	9,570
22	57,739	1.4	80.62	SK83		11,576	12,073	15,981	6,822	7,123
19	66,849	1.9	93.34	SK93		14,283	14,780	18,428	9,529	9,570

* M13G NEMA C-Face - Please allow additional week for delivery.

**AGMA CLASS II
EXPLOSION PROOF
25 HP**

AGMA CLASS II EXPLOSION PROOF 25 HP					C-FACE				REDUCER w/NEMA C-FACE ADAPTER FRAME 280TC	REDUCER w/NEMA C-FACE ADAPTER FRAME 320TC
					NORD OR OTHER "INQUIRE"	BALDOR MOTOR				
						DRILL RIG DUTY CM7058T-I 284TC TEFC 230/460V CONSTANT	IDXM7058T M13G * 284TC TEFC 230/460V 2:1 CT	IDXM7558T M13G * 324TC TEFC 230/460V 10:1 CT		
RPM	INCH LBS	AGMA S.F.	GEAR RATIO	GEAR MODEL						
1,419	1,110	2.2	1.24	SK51E		\$ 8,056	\$ 10,702	N/A	\$ 2,140	N/A
1,222	1,289	2.1	1.44							
1,158	1,361	2.0	1.52							
1,073	1,468	1.9	1.64							
967	1,629	1.8	1.82							
854	1,844	1.8	2.06							
704	2,238	1.7	2.50							
633	2,489	3.1	2.78	SK52		8,391	11,037	N/A	2,475	N/A
545	2,892	2.9	3.23							
518	3,044	2.9	3.40							
480	3,286	2.8	3.67							
431	3,653	2.7	4.08							
402	3,921	2.9	4.38							
382	4,127	2.5	4.61							
346	4,548	2.6	5.08							
314	5,013	2.1	5.60							
304	5,183	2.4	5.79							
289	5,452	2.4	6.09							
274	5,747	2.3	6.42							
242	6,508	2.1	7.27							
229	6,893	2.0	7.70							
200	7,860	3.4	8.78	SK62		9,797	12,443	15,238	3,881	4,188
199	7,905	1.9	8.83	SK52		8,391	11,037	N/A	2,475	N/A
166	9,472	1.6	10.58							
152	10,376	2.6	11.59	SK62		9,797	12,443	15,238	3,881	4,188
131	12,041	1.4	13.45	SK52		8,391	11,037	N/A	2,475	N/A
123	12,829	2.8	14.33	SK72		10,384	13,030	15,803	4,468	4,753
111	14,145	1.9	15.80	SK62		9,797	12,443	15,238	3,881	4,188
104	15,094	2.4	16.86	SK72		10,384	13,030	15,803	4,468	4,753
102	15,497	1.8	17.31	SK63		9,904	12,550	N/A	3,988	N/A
98	16,114	2.7	18.00	SK73		10,679	13,325	16,102	4,763	5,052
97	16,240	1.7	18.14	SK62		9,797	12,443	15,238	3,881	4,188
85	18,594	1.5	20.77	SK63		9,904	12,550	N/A	3,988	N/A
80	19,677	1.4	21.98							
75	20,895	2.1	23.34	SK73		10,679	13,325	16,102	4,763	5,052
62	25,353	1.7	28.32							
53	29,758	1.5	33.24							
45	34,986	2.3	39.08	SK83		13,039	15,685	19,351	7,123	8,301
40	39,731	2.0	44.38							
34	46,114	1.7	51.51							
28	55,406	1.4	61.89							
25	63,007	2.8	70.38	SK103		18,996	21,642	24,404	13,080	13,354
24	64,878	1.8	72.47	SK93		15,486	18,132	20,919	9,570	9,869
22	72,873	2.5	81.40	SK103		18,996	21,642	24,404	13,080	13,354

* M13G NEMA C-Face - Please allow additional week for delivery.

**AGMA CLASS II
EXPLOSION PROOF
30 HP**

AGMA CLASS II EXPLOSION PROOF 30 HP					C-FACE				REDUCER w/NEMA C-FACE ADAPTER FRAME 280TC	REDUCER w/NEMA C-FACE ADAPTER FRAME 320TC
					NORD OR OTHER "INQUIRE"	BALDOR MOTOR				
						DRILL RIG DUTY CM7060T-I 286TC TEFC 230/460V CONSTANT	IDXM7060T M13G * 286TC TEFC 230/460V 2:1 CT	IDXM7560T M13G * 326TC TEFC 230/460V 10:1 CT		
RPM	INCH LBS	AGMA S.F.	GEAR RATIO	GEAR MODEL						
1,419	1,332	1.8	1.24	SK51E		\$ 8,827	\$ 12,069	N/A	\$ 2,140	N/A
1,222	1,547	1.7	1.44							
1,158	1,633	1.7	1.52							
1,073	1,762	1.6	1.64							
967	1,955	1.5	1.82							
854	2,213	1.5	2.06							
704	2,686	1.4	2.50							
633	2,987	2.6	2.78	SK52		9,162	12,404	N/A	2,475	N/A
545	3,470	2.4	3.23							
518	3,653	2.4	3.40							
480	3,943	2.4	3.67							
431	4,383	2.3	4.08							
402	4,705	2.4	4.38							
386	4,899	3.3	4.56	SK62		10,568	13,810	16,524	3,881	4,188
382	4,952	2.1	4.61	SK52		9,162	12,404	N/A	2,475	N/A
346	5,457	2.2	5.08							
333	5,683	2.9	5.29	SK62		10,568	13,810	16,524	3,881	4,188
314	6,016	1.7	5.60	SK52		9,162	12,404	N/A	2,475	N/A
304	6,220	2.0	5.79							
289	6,542	2.0	6.09							
277	6,822	2.5	6.35	SK62		10,568	13,810	16,524	3,881	4,188
274	6,897	1.9	6.42	SK52		9,162	12,404	N/A	2,475	N/A
242	7,810	1.8	7.27							
233	8,122	3.3	7.56	SK62		10,568	13,810	16,524	3,881	4,188
229	8,272	1.7	7.70	SK52		9,162	12,404	N/A	2,475	N/A
199	9,486	1.6	8.83							
167	11,334	2.4	10.55	SK62		10,568	13,810	16,524	3,881	4,188
152	12,451	2.2	11.59							
141	13,450	2.7	12.52	SK72		11,155	14,397	17,089	4,468	4,753
126	14,954	1.8	13.92	SK62		10,568	13,810	16,524	3,881	4,188
123	15,395	2.3	14.33	SK72		11,155	14,397	17,089	4,468	4,753
111	16,974	1.6	15.80	SK62		10,568	13,810	16,524	3,881	4,188
104	18,113	2.0	16.86	SK72		11,155	14,397	17,089	4,468	4,753
97	19,488	1.4	18.14	SK62		10,568	13,810	16,524	3,881	4,188
75	25,074	1.8	23.34	SK73		11,450	14,692	17,388	4,763	5,052
62	30,424	1.5	28.32							
54	34,936	2.2	32.52	SK83		13,810	17,052	20,637	7,123	8,301
45	41,983	1.9	39.08							
40	47,677	1.6	44.38							
38	50,030	2.2	46.57	SK93		16,257	19,499	22,205	9,570	9,869
34	55,337	1.4	51.51	SK83		13,810	17,052	20,637	7,123	8,301
33	56,916	3.1	52.98	SK103		19,767	23,009	25,690	13,080	13,354
33	57,797	1.9	53.80	SK93		16,257	19,499	22,205	9,570	9,869
29	65,220	2.7	60.71	SK103		19,767	23,009	25,690	13,080	13,354
29	66,208	1.7	61.63	SK93		16,257	19,499	22,205	9,570	9,869
25	75,609	2.3	70.38	SK103		19,767	23,009	25,690	13,080	13,354
24	77,854	1.5	72.47	SK93		16,257	19,499	22,205	9,570	9,869
22	87,447	2.1	81.40	SK103		19,767	23,009	25,690	13,080	13,354

* M13G NEMA C-Face - Please allow additional week for delivery.

**AGMA CLASS II
EXPLOSION PROOF
40 HP**

AGMA CLASS II EXPLOSION PROOF 40 HP					C-FACE				REDUCER w/NEMA C-FACE ADAPTER FRAME 320TC	REDUCER w/NEMA C-FACE ADAPTER FRAME 360TC
					NORD OR OTHER "INQUIRE"	BALDOR MOTOR				
						DRILL RIG DUTY CM7062T-I 324TC TEFC 230/460V CONSTANT	IDXM7062T M13G * 324TC TEFC 230/460V 2:1 CT	IDXM7562T M13G * 364TC TEFC 230/460V 10:1 CT		
RPM	INCH LBS	AGMA S.F.	GEAR RATIO	GEAR MODEL						
598	4,218	3.3	2.97	SK62		\$ 13,228	\$ 17,555	\$ 19,188	\$ 4,188	\$ 5,388
538	4,687	3.2	3.30							
477	5,283	3.1	3.72							
454	5,553	3.0	3.91							
438	5,752	2.9	4.05							
389	6,476	2.8	4.56							
336	7,513	2.2	5.29							
317	7,954	2.9	5.60	SK72		13,793	18,120	19,665	4,753	5,865
280	9,019	1.9	6.35	SK62		13,228	17,555	19,188	4,188	5,388
276	9,118	2.7	6.42	SK72		13,793	18,120	19,665	4,753	5,865
255	9,871	3.3	6.95							
235	10,737	2.6	7.56	SK62		13,228	17,555	19,188	4,188	5,388
217	11,632	3.1	8.19	SK72		13,793	18,120	19,665	4,753	5,865
202	12,470	2.1	8.78	SK62		13,228	17,555	19,188	4,188	5,388
188	13,436	2.9	9.46	SK72		13,793	18,120	19,665	4,753	5,865
168	14,984	1.8	10.55	SK62		13,228	17,555	19,188	4,188	5,388
164	15,396	2.7	10.84	SK72		13,793	18,120	19,665	4,753	5,865
153	16,461	1.7	11.59	SK62		13,228	17,555	19,188	4,188	5,388
142	17,782	2.0	12.52	SK72		13,793	18,120	19,665	4,753	5,865
128	19,770	1.4	13.92	SK62		13,228	17,555	19,188	4,188	5,388
124	20,353	1.8	14.33	SK72		13,793	18,120	19,665	4,753	5,865
105	23,946	1.5	16.86							
99	25,565	1.7	18.00	SK73		14,092	18,419	20,305	5,052	6,505
86	29,286	1.5	20.62							
84	29,883	2.4	21.04	SK83		17,341	21,668	22,855	8,301	9,055
73	34,683	2.0	24.42							
63	39,810	1.8	28.03							
66	38,419	2.8	27.05	SK93		18,909	23,236	24,839	9,869	11,039
57	44,384	2.4	31.25							
55	46,188	1.6	32.52	SK83		17,341	21,668	22,855	8,301	9,055
47	53,829	3.3	37.90	SK103		22,394	26,721	28,224	13,354	14,424
45	55,505	1.4	39.08	SK83		17,341	21,668	22,855	8,301	9,055
45	56,158	1.9	39.54	SK93		18,909	23,236	24,839	9,869	11,039
39	64,268	2.8	45.25	SK103		22,394	26,721	28,224	13,354	14,424
38	66,143	1.6	46.57	SK93		18,909	23,236	24,839	9,869	11,039
34	75,247	2.4	52.98	SK103		22,394	26,721	28,224	13,354	14,424
33	76,411	1.4	53.80	SK93		18,909	23,236	24,839	9,869	11,039
29	86,225	2.1	60.71	SK103		22,394	26,721	28,224	13,354	14,424
25	99,959	1.8	70.38							
22	115,611	1.6	81.40							

* M13G NEMA C-Face - Please allow additional week for delivery.

**AGMA CLASS II
EXPLOSION PROOF
50 HP**

AGMA CLASS II EXPLOSION PROOF 50 HP					C-FACE				REDUCER w/NEMA C-FACE ADAPTER FRAME 320TC	REDUCER w/NEMA C-FACE ADAPTER FRAME 360TC
					NORD OR OTHER "INQUIRE"	BALDOR MOTOR				
						DRILL RIG DUTY CM7064T-I 326TC TEFC 230/460V CONSTANT	IDXM7064T M13G * 326TC TEFC 230/460V 2:1 CT	IDXM7564T M13G * 365TC TEFC 230/460V 10:1 CT		
RPM	INCH LBS	AGMA S.F.	GEAR RATIO	GEAR MODEL						
598	5,273	2.6	2.97	SK62						
538	5,859	2.5	3.30							
477	6,604	2.4	3.72							
454	6,942	2.3	3.91			\$ 14,412	\$ 19,216	\$ 21,716	\$ 4,188	\$ 5,388
438	7,190	2.3	4.05							
389	8,096	2.2	4.56							
336	9,392	1.8	5.29							
317	9,942	2.3	5.60	SK72		14,977	19,781	22,193	4,753	5,865
280	11,273	1.5	6.35	SK62		14,412	19,216	21,716	4,188	5,388
276	11,398	2.1	6.42	SK72		14,977	19,781	22,193	4,753	5,865
255	12,339	2.6	6.95							
235	13,422	2.0	7.56	SK62		14,412	19,216	21,716	4,188	5,388
217	14,540	2.4	8.19	SK72		14,977	19,781	22,193	4,753	5,865
202	15,588	1.7	8.78	SK62		14,412	19,216	21,716	4,188	5,388
188	16,795	2.3	9.46	SK72		14,977	19,781	22,193	4,753	5,865
168	18,730	1.5	10.55	SK62		14,412	19,216	21,716	4,188	5,388
164	19,245	2.1	10.84	SK72		14,977	19,781	22,193	4,753	5,865
142	22,227	1.6	12.52							
124	25,441	1.4	14.33							
107	29,400	2.0	16.56	SK83		18,525	23,329	25,383	8,301	9,055
93	33,945	2.8	19.12	SK93		20,093	24,897	27,367	9,869	11,039
84	37,353	1.9	21.04	SK83		18,525	23,329	25,383	8,301	9,055
77	40,780	2.6	22.97	SK93		20,093	24,897	27,367	9,869	11,039
73	43,354	1.6	24.42	SK83		18,525	23,329	25,383	8,301	9,055
70	44,916	2.7	25.30	SK103		23,578	28,382	30,752	13,354	14,424
66	48,023	2.2	27.05	SK93		20,093	24,897	27,367	9,869	11,039
63	49,763	1.4	28.03	SK83		18,525	23,329	25,383	8,301	9,055
57	55,480	1.9	31.25	SK93		20,093	24,897	27,367	9,869	11,039
47	67,286	2.6	37.90	SK103		23,578	28,382	30,752	13,354	14,424
45	70,197	1.5	39.54	SK93		20,093	24,897	27,367	9,869	11,039
39	80,335	2.2	45.25	SK103		23,578	28,382	30,752	13,354	14,424
34	94,058	1.9	52.98							
29	107,782	1.6	60.71							
25	124,949	1.4	70.38							

* M13G NEMA C-Face - Please allow additional week for delivery.

**AGMA CLASS II
EXPLOSION PROOF
60 HP**

					C-FACE		REDUCER w/NEMA C-FACE ADAPTER FRAME 360TC
					NORD OR OTHER "INQUIRE"	BALDOR MOTOR	
RPM	INCH LBS	AGMA S.F.	GEAR RATIO	GEAR MODEL		IDXM7066 M13G * 364TC TEFC 230/460V 2:1 CT	
598	6,327	2.7	2.97	SK62		\$ 22,473	\$ 5,388
538	7,030	2.5	3.30				
477	7,925	2.3	3.72				
454	8,330	2.1	3.91				
438	8,628	1.9	4.05				
431	8,777	2.7	4.12	SK72		22,950	5,865
389	9,715	1.9	4.56	SK62		22,473	5,388
366	10,333	2.5	4.85	SK72		22,950	5,865
336	11,270	1.5	5.29	SK62		22,473	5,388
317	11,930	2.1	5.60	SK72		22,950	5,865
276	13,677	1.8	6.42				
255	14,806	2.6	6.95				
235	16,106	1.7	7.56	SK62		22,473	5,388
217	17,448	2.4	8.19	SK72		22,950	5,865
202	18,705	1.4	8.78	SK62		22,473	5,388
188	20,154	2.1	9.46	SK72		22,950	5,865
164	23,094	1.8	10.84				
150	25,224	2.5	11.84	SK82		25,134	8,049
124	30,444	1.9	14.29				
107	35,280	1.6	16.56				
93	40,734	2.6	19.12	SK93		28,124	11,039
84	44,824	1.6	21.04	SK83		26,140	9,055
77	48,936	2.2	22.97	SK93		28,124	11,039
73	52,025	1.4	24.42	SK83		26,140	9,055
70	53,900	3.3	25.30	SK103		31,509	14,424
66	57,628	1.9	27.05	SK93		28,124	11,039
57	66,576	1.6	31.25				
47	80,743	2.2	37.90	SK103		31,509	14,424
39	96,402	1.8	45.25				
34	112,870	1.5	52.98				
29	129,338	1.4	60.71				

* M13G NEMA C-Face - Please allow additional week for delivery.